

ZRB15XR61A106ME01#

Note: This datasheet may be out of date.

Please download the latest datasheet of ZRB15XR61A106ME01# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=ZRB15XR61A106ME01%23

"#" indicates a package specification code.















mobile devices

< List of part numbers with package codes > ZRB15XR61A106ME01D ZRB15XR61A106ME01J



Applications

Unsuitable	Please be sure to read and comply with	
Applications	these "Precautions for use."	
Specific Applications	Mobile Electronics	
	Please refer to Our Website and	
	specifications, etc. for information about	
	the performance, functions, quality,	
	management, and safety required for	
	the above applications, and use	
	Products after confirming the	
	performance and reliability of the actual	
	Product.	




Notices


Derating1. Only for mobile devices



Appearance & Shape









References

Packaging	Specifications	Standard Packing Quantity
D	180mm Paper Tape	8000
J	330mm Paper Tape	30000

Mass (typ.)	
1 piece	2.8mg

1 of 2

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





ZRB15XR61A106ME01#

Note: This datasheet may be out of date.

Please download the latest datasheet of ZRB15XR61A106ME01# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=ZRB15XR61A106ME01%23

"#" indicates a package specification code.



Specifications

Length	1.0±0.22mm
Width	0.5±0.2mm
Thickness	0.65±0.2mm
Capacitance	10μF ±20%
Distance between external terminals g	0.3mm min.
External terminal size e	0.1 to 0.4mm
Operating Temperature Range	-55°C to 85°C
Rated Voltage	10Vdc
Size code in inch(mm)	0402 (1005M)
Capacitance change rate	±15.0%
Temperature characteristics (complied standard)	X5R(EIA)
Temperature range of temperature characteristics	-55°C to 85°C

2 of 2

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

