



Cable Tie, Min, 5.6in, Nyl, BU, PK1000

PLT1.5M-M6

Pan-Ty® locking tie, miniature cross section, 5.6 (142mm) length, nylon 6.6, blue.

 **Discontinued**

Suggested Replacement Parts:

PLT2M-M6

Note: It is the buyer's responsibility to determine if the suggested replacement part is suitable for your application and intended use.

Specifications

Material Description	Nylon 6.6
Product Type	Cable Tie
Sub Brand	Pan-Ty®
Color	Blue
Material	Nylon 6.6
Overall Length (mm)	142
Body Width (mm)	2.5
Body Thickness (In.)	0.043
Body Thickness (mm)	1.1
Maximum Bundle Diameter (mm)	31.8
Minimum Bundle Diameter (In.)	0.06
Minimum Bundle Diameter (mm)	1.5
Minimum Loop Tensile Strength (N)	80
Minimum Loop Tensile Strength (lb)	18
Maximum Operating Temperature (°C)	85
Maximum Operating Temperature (°F)	115
Minimum Operating Temperature (°C)	-60
Minimum Operating Temperature (°F)	-76
Minimum Installation Temperature (°C)	-20
Minimum Installation Temperature (°F)	-4
Standards Met	UL Recognized (File #E56854), UL 62275 Compliant (Type 2, 21), RoHS Compliant
For Use With	GTS-E, GS2B-E, PTS
Part Features	One-piece locking wedge for consistent performance and reliability. Low thread force and high loop tensile strength.

Packaging Detail

UPC	07498356024
Std. Pkg. Qty.	1000
Std. Pkg. Volume (cf)	0.0793
Std. Ctn. Qty.	50000
Std. Ctn. Volume (cf)	3.9670