





PART NUMBER	LED COLOR (nm)
5988C10102F	RED (625)
5988C10107F	
5988C30102F	ORANGE (605)
5988C30107F	
5988C40102F	YELLOW (590)
5988C40107F	
5988C60102F	YELLOW GREEN (570)
5988C60107F	
5988C80102F	GREEN (525)
5988C80107F	
5988C90102F	BLUE (470)
5988C90107F	

REV	REVISIONS	DRN	APP	DATE
A	NEW RELEASE	LD	NO	3-22-19




SMT Reflow Soldering Instructions SMT





ABSOLUTE MAXIMUM RATINGS AT 25° C							
LED COLOR	POWER DISSIPATON (mW)	FORWARD CURRENT (mA)	PEAK FORWARD CURRENT (mA)	REVERSE VOLTAGE (V)	OPERATING TEMPRATURE (° C)	STORAGE TEMPRATURE (° C)	DERATING CURVE (mA/° C)
RED	48	20	60	5	-40 TO +85	-40 TO +100	.49
ORANGE	70						.45
YELLOW	48						.51
YELLOW GREEN	48						.49
GREEN	70						.57
BLUE	70						.51

MARK	DEFINITION	CONDITION
$T_{S_{max}}$	Maximum of pre-heating temperature	200° C
$T_{S_{min}}$	Minimum of pre-heating temperature	150° C
T_s	Time form $T_{S_{min}}$ to $T_{S_{max}}$	60-120 sec
T_L	Reference temperature	217° C
t_L	Retention time for T_L	within 60s
T_P	Peak Temperature	260° C
t_P	Time for peak temperature	within 10s
DT_r/Dt	Temperature rising rate	under 3° C/sec
DT_d/Dt	Temperature decreasing rate	under -3° C/sec



OPERATING CHARACTERISTICS AT 25° C										
LED COLOR	IF (mA)	LUMINOUS INTENSITY (mcd)			DOMINANT WAVELENGTH (nm)			REVERSE CURRENT MAX	FORWARD VOLTAGE IF=5mA	
		MIN.	TYP.	MAX.	MIN.	TYP.	MAX.		TYP.	MAX.
RED	20	280	405	530	620	625	630	10 μ A @ VR=5V	1.8	2.4
ORANGE		230	290	350	600	605	610		1.8	2.4
YELLOW		280	405	530	585	590	595		1.8	2.4
YELLOW GREEN		40	65	90	565	570	575		1.8	2.4
GREEN		1500	1900	2300	520	525	530		2.8	3.3
BLUE		350	440	530	465	470	475		2.8	3.3

RECOMMENDED RoHS SOLDER PROFILE



ATTENTION:
OBSERVE PRECAUTIONS FOR
HANDLING ELECTROSTATIC
SENSITIVE DEVICES

NOTES:

- PIN NUMBERS ARE FOR REFERENCE ONLY, DESIGNATION NON-EXISTENT ON PART.
- LABELING FOR REEL AND OUTSIDE OF ALUMINUM BAG, DIALIGHT P/N, QUANTITY PER REEL, DATE CODE, INTENSITY BIN CODE, LOT NUMBER AND COUNTRY OF ORIGIN
- THIS PRODUCT IS RoHS COMPLIANT. EACH BAG IS TO BE MARKED WITH RoHS COMPLIANT LABEL OR EQUIVALENT MARKINGS. LED MUST BE Pb FREE.
- MOISTURE SENSITIVITY LEVEL 3
- QUANTITY IS 3,000 PCS/ REEL

THIS DRAWING AND THE CONTENTS HEREIN ARE CONFIDENTIAL AND THE SOLE PROPERTY OF DIALIGHT CORP. REPRODUCTION OF THIS DRAWING OR CONSTRUCTION OF ANY PARTS WITHIN THIS DRAWING ARE FORBIDDEN WITHOUT THE WRITTEN CONSENT OF DIALIGHT CORP.		
DIALIGHT CORP INTERNAL REFERENCE ONLY = 3D MODEL : 4500521848X15-A-1		
SCALE: 35.00	DRAWING NUMBER	REV
ALL DIM'S IN: INCHES (MM)	C18403	A
TOLERANCES: UNLESS OTHERWISE SPECIFIED	TITLE	
FRACTIONS: ±1/64	MINI-PLCC2 PACKAGE	
DECIMALS (.XX): ±.01	MATERIAL	
DECIMALS (.XXX): ±.005		
DECIMALS (.XXXX): ±.0005		
ANGLES: ±1°	FINISH	
FSCM 83330	1501 ROUTE 34 SOUTH FARMINGDALE, NJ 07727 (732) 919-3119 www.dialight.com	
SHEET 1 OF 1		FAMILY TABLE: